

Serial NO. 10/822,715
Amendment
Responsive to Office Action dated September 10, 2007

NIT-420

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A biomagnetic measurement apparatus comprising means for detecting a magnetic field produced from a heart, means for calculating current vectors from said detected magnetic field, means for calculating a potential waveform corresponding to a ventricular muscle cell action potential based on the change of absolute values of said current vectors with time, and means for displaying said potential waveform;

wherein in said means for calculating a potential waveform, said potential waveform is calculated by adding the absolute values of said current vectors in a period from a start time of depolarization of the heart to an end time of depolarization of the heart, and said potential waveform is calculated by subtracting the absolute values of said current vectors from the value of said potential waveform at the end of depolarization of the heart in a period from the end of depolarization of the heart to an end time of repolarization of the heart.

2. (Original) The biomagnetic measurement apparatus according to claim 1, wherein said magnetic fields are detected at a plurality of different measurement points, said current vectors are calculated at said plurality of measurement points, and said potential waveforms obtained based on the change of the absolute values of said current vectors with time are displayed.

Serial NO. 10/822,715

NIT-420

Amendment

Responsive to Office Action dated September 10, 2007

3. (Canceled)

4. (Original) The biomagnetic measurement apparatus according to claim 1, wherein said means displaying a potential waveform displays the waveform of said measured magnetic field and said potential waveform at the same time.

5. (Original) A biomagnetic measurement apparatus comprising a plurality of detection coils detecting, when a plane in parallel with a plane contacted with a living body is xy plane and an axis vertical to said (x, y) plane is z, element Bz in z direction of a magnetic field produced from said living body at a plurality of measurement points (x, y), a data collection device collecting detected signal data of the element Bz in said z direction, an operation processor performing operation processing of said collected signal data, and a display device displaying the result of said operation processing, wherein said operation processor executes first operation processing in which when $t = t_i$ ($i = 0, 1, \dots, m$) is a period corresponding to depolarization of the heart of said living body and $t = t_i$ ($i = m+1, m+2, \dots, n$) is a period corresponding to repolarization of the heart of said living body, from the element Bz in said z direction at time $t = t_i$ ($i = 0, 1, \dots, n$) at said measurement point (x, y), a current vector $(I_x(t), I_y(t))$ and an absolute value of said current vector $I_{xy}(t) = \sqrt{\{I_x(t)^2 + I_y(t)^2\}}$ are calculated, second operation processing in which when the lower limit of addition Σ is $i = 0$ and the upper limit of addition Σ is $i = 0, 1, \dots, m$, a potential waveform in a period corresponding to depolarization of the heart of said living body is calculated by using $V(t_i) = \Sigma I_{xy}(t_i)$, and third operation processing in which when the value of said potential waveform V

Serial NO. 10/822,715

NIT-420

Amendment

Responsive to Office Action dated September 10, 2007

(t_m) at the end of a period corresponding to depolarization of the heart of said living body is V_m , the lower limit of addition Σ is $i = m+1$ and the upper limit of addition Σ is $i = m+1, m+2, \dots, n$, a potential waveform in a period corresponding to repolarization of the heart of said living body is calculated by using $V(t_i) = V_m - \Sigma I_{xy}(t_i)$, and said display device displays said potential waveform corresponding to said measurement point (x, y) obtained by said second and said third operation processing.

6. (Original) The biomagnetic measurement apparatus according to claim 5, wherein said potential waveforms V are calculated at said plurality of measurement points.

7. (Original) The biomagnetic measurement apparatus according to claim 6, wherein said display device displays the waveforms of said measured magnetic fields and said potential waveforms V .

8. (Original) The biomagnetic measurement apparatus according to claim 6, wherein said display device performs contour map display of said potential waveforms V .

9. (Currently Amended) A biomagnetic measurement apparatus, wherein in which when a plane in parallel with a plane contacted with the surface of a chest is xy plane and an axis vertical to said x, y plane is z, magnetic fields produced from a heart are detected at a plurality of measurement points (x, y) to calculate current vectors from said detected magnetic fields, wherein when start time of depolarization of the heart is t_0 , end time of depolarization of

Serial NO. 10/822,715

NIT-420

Amendment

Responsive to Office Action dated September 10, 2007

the heart is t_m , end time of repolarization of the heart is t_n , an absolute value of said current vector at time t_i is $I_{xy}(t_i)$ ($i = 1, 2, \dots, n$), and a potential waveform at said time t_0 is $V(t_0) = 0$, a potential waveform at time t_i in a period from said time t_0 to said time t_m is calculated by using $V(t_i) = V(t_{i-1}) + I_{xy}(t_i)$, the value of potential waveform $V(t_m)$ at said time t_m is V_m , a potential waveform at said time t_{m+1} is calculated by using $V(t_{m+1}) = V_m - I_{xy}(t_{m+1})$, a potential waveform at time t_i in a period from time t_{m+2} to time t_n is calculated by using $V(t_i) = V(t_{i-1}) - I_{xy}(t_i)$, and said potential waveform $V(t_i)$ is calculated at said measurement point (x, y) , and said potential waveform is displayed.

10. (Original) The biomagnetic measurement apparatus according to claim 9, wherein said potential waveforms corresponding to said plurality of measurement points (x, y) are displayed at the same time.

11. (Currently Amended) A biomagnetic measurement apparatus, wherein ~~in which~~ when a plane in parallel with a plane contacted with the surface of a chest is an xy plane and an axis vertical to said xy plane is z, magnetic fields produced from a heart are detected at a plurality of measurement points (x, y) to calculate current vectors, wherein in a period from a start time of depolarization of the heart to an end time of depolarization of the heart, absolute values of said current vectors are added to calculate a potential waveform, and in a period from the end of depolarization of the heart to an end time of repolarization of the heart, the absolute values of said current vectors are subtracted from the value of said potential waveform at the end of depolarization of the heart to calculate said potential waveform at said measurement

Serial NO. 10/822,715

NIT-420

Amendment

Responsive to Office Action dated September 10, 2007

point (x, y) to display said potential waveform.

12. (Currently Amended) A biomagnetic measurement apparatus which detects a magnetic field produced from a heart to calculate current vectors, ~~further~~ comprising a display device displaying a potential waveform corresponding to a ventricular muscle cell action potential obtained based on the change of the absolute values of said current vectors with time, wherein in a period from start time of depolarization of the heart to an end time of depolarization of the heart, said potential waveform is calculated by adding absolute values of said current vectors, and in a period from the end of depolarization of the heart to an end time of repolarization of the heart, said potential waveform is calculated by subtracting the absolute values of said current vectors from the value of said potential waveform at the end of depolarization of the heart.

13. (Original) The biomagnetic measurement apparatus according to claim 12, wherein said magnetic fields are detected at a plurality of measurement points, said current vectors are calculated at said plurality of measurement points, and said potential waveforms obtained based on the change of the absolute values of said current vectors with time are displayed on said display device.

14. (Canceled)

Serial NO. 10/822,715

NIT-420

Amendment

Responsive to Office Action dated September 10, 2007

15. (Original) The biomagnetic measurement apparatus according to claim 12, wherein said display device displays the potential waveform of said measured magnetic field and said potential waveform at the same time.

16 - 17. (Canceled)